

Misuratore di luce digitale GM1010



Features:

- Measuring range
0Lux - 200,000 lux/0Fc - 185,806Fc
- Automatic measurement function
- LUX/FC Unit selection function
- Data rise and fall time is short
- After 5 minute Auto power off
- MAX/MIN measurements
- Low battery indication
- Backlight function
- Power supply:
6F22 9V battery

Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Progettato con un basso consumo energetico e un software di autodeterminazione per un'elevata precisione e affidabilità

La retroilluminazione consente al dispositivo di funzionare in un ambiente buio

Adatto per casa, negozio di lavoro, ufficio, utilizzo del monitoraggio della luce

Aggiornamenti digitali: 2 volte al secondo

Sensore fotometrico: Diodo al silicio

Durata della batteria: oltre 60 ore

Spegnimento automatico: 5 minuti senza alcun funzionamento

Specifications

Product Code	XE-4005-001
Model	GM1010 Digital Light Meter
Accuracy	±3% RDG ±0.5% FS (10,000lux) ±4%RDG ±10 digits (>10,000lux)
Ambient Operating Temperature	0 to 40°C, 10-90% RH
Battery	9V battery
Dimensions	166 x 52.5 x 35.5 mm
Function #1	Backlight allows the device to work in a dark environment
Function #2	Fit for home, work shop, office, light monitoring usage
Function #3	Digital Updates: 2 Times/Second
Function #4	Photometric Sensor: Silicon Diode
Function #5	Auto Power Off: 5 minutes without any operating
Input / Ranges	0-200,000 lux/O Fc-185, 806 Fc
Operating Temperature	0 to 40°C, 10-90% RH
Weight	146.1g (including battery)



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Power Consumption	Battery Life: More than 60 hours
Storage Temperature	-20 to 40°C, 10-90% RH