



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

Sonda industriale Pt100 a resistenza al platino con prolunga in ritardo. Sonda da 150 mm x 8,0 mm con inserto da 275 mm x 6,0 mm



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Hai bisogno di calibrare il tuo sensore di temperatura?

Tracciabile secondo gli standard di calibrazione ISO17025 (UKAS), Labfacility offre la possibilità di scegliere tra una calibrazione tracciabile a 3 o 5 punti utilizzando la nostra funzione di calibrazione interna, possibile selezionare qualsiasi punto di temperatura tra -10C e +200C.

Tieni presente che se aggiungi un'opzione di calibrazione al tuo ordine, verrai contattato per informazioni sulla consegna.

Indicazioni**Specifications**

Product Code	XE-3640-001
Sensor Type	Pt100 (100 Ohms @ 0°C) to IEC 751
Insert	6.0mm diameter 316 stainless steel terminated with spring loaded ceramic connection block
Process Connection	1/2"BSP parallel
Cable Connection	M20 x 1.5mm cable entry (gland included)
Termination Type	IP67 aluminium alloy weatherproof KNE connection head
Max. Temperature	+450°C (connection head @ 170°C)
Min. Temperature	-50°C
Tolerance	Class B
Number of Wires	4
Probe Material	8.0mmO 316 stainless steel below 1/2"BSP parallel process connection 1/2" diameter x 75mm lagging length to underside of connection head