


Cavo termocoppia / filo tipo K PVC adereto a chiesta piatta (BS)

Type K, 13/0.2mm
PVC Flat Pair



Cavo termocoppia / filo tipo K PVC adereto a chiesta piatta (BS)

L'immagine è solo per l'illustrazione di codifica a colori

Il prezzo è per metro - si prega di aggiungere la quantità necessaria per il cesto. Solo 613 metri rimasti in magazzino

Il cavo di compensazione assomiglia alla caratteristica termoelettrica della termocoppia pertinente su un intervallo di temperatura ambiente limitato, da 0 a 80 gradi centigradi in genere. Poiché questi cavi sono realizzati con materiali a basso costo, è possibile ottenere risparmi sui costi per gli impianti rispetto all'esecuzione di un vero cavo di estensione thermocouple.

Indicazioni**Specifications**

Product Code	WK-010-D
General Description	Good general purpose insulation for 'light' environments. Waterproof and very flexible.
Cable Length	Priced per metre
Cable Type	Flat pair construction
Core / Strands	13/0.2mm
Outer Colour	Red
+ Colour	Brown
- Colour	Blue
Insulation Material	PVC Insulated
Max. Temperature	+105°C
Min. Temperature	-10°C
+ Conductor	Nickel Chromium



LABFACILITY

TEMPERATURE & PROCESS TECHNOLOGY

- Conductor	Nickel Aluminium
Standards Met	BS
Thermocouple Type	K
Tolerance	Class 2